

**TWISTED KNOT WIRE CUP F-25 Ø 65/ M-10x1,5/
0,50 STEEL/ DISPLAY**

CODE: 250601EKM15D



BRUSH DIAMETER: 65 mm. / 2.3/4"

NUT: M-10x1,5

TRIM LENGTH: 22 mm. / 7/8"

WIRE: Steel Ø0,50 mm. / Ø.020"

KNOT: 18 knots Ø10mm. / Ø3/8".

PACKING: 12 units per box.

R.P.M. MAX: 13.000.

APPLICATIONS AND USES: Specially designed for High Speed (11.000 r.p.m.) light mini-grinders. Suitable for continuous and frequent brushing (shipyards, metal structures, maintenance welds, etc.) Comfortable use and elimination of human fatigue. Special design allowing access to angles.

STANDARDS: Manufactured under the EN 1083 European Standards

SAFETY WARNINGS: Always use safety goggles, clothes and suitable equipment. Do not use brushes in machines whose speeds are greater than the maximum speed of the brush. Do not remove any protective equipment from the machine. Do not use brushes in poor condition. Rust or any other type of chemical alteration to the wire can affect the performance of the brush. Keep the brushes stored on shelves, containers or boxes so that they are protected from the effects of the environment (damp, acids, gases, etc.).

DATE 14/01/2020	APPROVED BY:  QUALITY DEPARTMENT MANAGER ENEKO SALABERRIA	FECIN cepillería industrial Polig. Ind. de ITZIAR, Parcela H / 7 Apdo. 1 • 20820 DEBA • Gipuzkoa (España) Tif.: +34 943 19 92 84 • Fax: +34 943 19 93 17 fecin@fecin.es
------------------------	---	--