SDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE SDS FOR:

PRODUCT: AC90 Multipurpose Lubricant

DATE: 25-Apr-14

(SDS date)

1. Manufacturer/Supplier: Tradegear Ltd

Level 1, 99 Clarence Street

Riccarton

Christchurch 8011 New Zealand

Phone: 0800 22 44 34 or +64 3 331 6517 Fax: 0800 22 11 51 or +64 9 522 8833 24 hr emergency contact: +64 21 510 624

Website: www.tradegear.co.nz Email: office@tradegear.co.nz

Emergency Information: National Poison Centre: 0800 764 766

Chemcall 24/7 Emergency Response Service: 0800 243 622

13. Disposal Considerations: Product

Recommendation - Consult local or national regulations to ensure proper disposal.

Packaging

Disposal must be made according to official regulations.

16. Other Information: Employers should use this information only as a supplement to other information gathered

by them and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.





AC-90 Multipurpose Lubricant

SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Telephone

Product Name AC-90 Multipurpose Lubricant.
Trade Name AC-90 Multipurpose Lubricant.
Part No. 1839, 1943, 1994, 2006

CAS No. Mixture.
EINECS No. Mixture.
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified use(s) Cleaner, Lubricant, Anti –Rust fluid, Displaces Moisture, Removes

sticky deposits, removes rust marks. Do not mix with other chemicals.

Uses advised against

1.3 Details of the supplier of the Safety Data Sheet

Company Identification Action Can Ltd.,

Dixon Close,

Old Boston Trading Estate, Haydock, St. Helens, Merseyside. WA11 9SF. 00 44 1942 713667 01942 716235

info@actioncan.com

E-Mail (competent person)

Emergency telephone number

Emergency Phone No. 01942 713667 (Mon - Fri: 9am to 5pm)

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Hazard statement(s)

Regulation (EC) No. 1272/2008 (CLP) Aerosol 1; Extremely flammable aerosol. Pressurised container: May

burst if heated.

STOT SE 3; May cause drowsiness or dizziness.

Aquatic Chronic 3; Harmful to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name AC-90 Multipurpose Lubricant.

Hazard pictogram(s)





GHS02

GHS07

Signal word(s) Danger.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated. H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

EUH066: Repeated exposure may cause skin dryness or cracking.

Revision: 6 Page: 1/7 Date: April 2014-04-25





Certificate Number 768 ISO 9001

AC-90 Multipurpose Lubricant

Precautionary statement(s) P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing vapours.

P410+P412: Protect from sunlight. Do no expose to temperatures

exceeding 50°C/122°F.

Additional Information Keep out of reach of children.

Do not spray on a naked flame or any incandescent material.

This product is aerosol packed and in a limited quantity as such it is

unlikely to pose a significant spill or environmental hazard.

2.3 Other hazards None.

2.4 Additional Information For full text of H/P phrases see section 16.

Gloves advised as general industrial good practice.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

3.1 Mixtures

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH	Hazard pictogram(s) and	
				Registration No.	Hazard statement(s)	
Naphtha (petroleum),	50 - 75	64742-48-9	265-150-3	None assigned	GHS02, Flam. Liq. 3; H226,	
hydrotreated heavy					GHS07, STOT SE 3; H336,	
					GHS08, Asp. Tox. 1; H304,	
					Aquatic Chronic 3; H412,	
					EUH066	
Butane	10 - 25	106-97-8	203-447-8	None assigned	GHS02, Flam. Gas 1; H220,	
					GHS04, Press. Gas:	
					Liquefied gas; H280	
Isobutane	10 - 25	75-28-5	200-857-2	None assigned	GHS02, Flam. Gas 1; H220,	
					GHS04, Press. Gas:	
					Liquefied gas; H280	

3.2 Additional Information

For full text of H/P phrases see section 16.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for

breathing. Call a POISON CENTER/doctor if you feel unwell. Wash affected skin with soap and water. Remove any contaminated

Skin Contact Wash affected skin with soap and water. Remove any contaminated clothing, do not keep cloths contaminated with this product in

overall pockets or next to skin.

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20

minutes. If symptoms persist, obtain medical attention.

Revision: 6 Page: 2/7 Date: April 2014-04-25



Certificate Number 768 ISO 9001

AC-90 Multipurpose Lubricant

Ingestion Unlikely route of exposure. Wash out mouth with water. Do not

induce vomiting. Risk of aspiration.

4.2 Most important symptoms and effects, both acute Repeated exposure may cause skin dryness or cracking. Vapours and delayed may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and Unlikely to be required but if necessary treat symptomatically.

special treatment needed

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

> Suitable Extinguishing Media Extinguish preferably with dry chemical, sand or carbon dioxide.

Unsuitable Extinguishing Media Water jet spray.

5.2 Special hazards arising from the substance or mixture

5.3 Advice for fire-fighters Heating may cause pressure rise with risk of bursting.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions. Keep fire exposed containers cool by spraying

with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

Eliminate sources of ignition. Ensure adequate ventilation. Stop 6.1 Personal precautions, protective equipment and

> leak if safe to do so. Avoid breathing vapours. Wear protective gloves.

6.2 Environmental precautions Do not allow to enter drains, sewers or watercourses. Spillages or

uncontrolled discharges into watercourses must be alerted to the

appropriate regulatory body.

6.3 Methods and material for containment and cleaning Place leaking cans in a bucket or pail to minimise product

6.4

emergency procedures

contamination of surfaces. Collect spillage. Absorb remaining liquid in sand or inert absorbent and remove to safe place. Transfer to a

container for disposal. Do NOT wash away into sewer. Containers must not be punctured or destroyed by burning, even when empty.

Reference to other sections See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Keep away from heat, hot surfaces, sparks, open flames and other Precautions for safe handling

ignition sources. No smoking. Keep away from: Electrostatic charge. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not let the can touch battery terminals, electrical connectors or any source of electricity. Use product in a well-ventilated area only. Ensure adequate ventilation. Avoid breathing vapours. Avoid prolonged skin contact. Wear

protective gloves.

7.2 Conditions for safe storage, including any

incompatibilities

Protect from sunlight. Store in a well-ventilated place. Industrial product for professional use. Locked storage does not apply to this

product.

Storage Temperature Do not expose to temperatures exceeding 50°C/122°F.

Storage Life Stable under normal conditions. Incompatible materials Oxidizing agents, Reducing agent.

7.3 Cleaner, Lubricant, Anti -Rust fluid, Displaces Moisture, Removes Specific end use(s)

sticky deposits, removes rust marks.

Revision: 6 Date: April 2014-04-25 Page: 3/7



AC-90 Multipurpose Lubricant

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA	LTEL (8 hr TWA	STEL	STEL	Note
		ppm)	mg/m³)	(ppm)	(mg/m ³)	
Butane	106-97-8	600	1450	750	1810	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit valueNot established.

8.1.3 PNECs and DNELs Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls Provide adequate ventilation.

8.2.2 Personal protection equipment Not normally required, but eye protection advised as good practice

for Industrial users. Take care to always spray away from your face.

Eye/face protection Not normally required.



Skin protection (Hand protection/Other)

Not normally required. Wear suitable gloves if prolonged skin

properties

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment. A suitable mask with filter type A (EN14387 or EN405)

may be appropriate.

contact is likely.

Thermal hazards Not applicable.

8.2.3 Environmental Exposure ControlsAvoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical

Appearance Aerosol.

Colour Pale brown.

Odour Characteristic.

Odour Threshold Not available.

pH Not applicable.

Melting Point/Freezing Point Not available.

Initial boiling point and boiling range

Not available.

Flash point Not applicable (Aerosol spray can)

43°C (Refers to product before aerosol packing)

Evaporation rate Not applicable.

Flammability (solid, gas) Aerosol 1; Extremely flammable aerosol.

Upper/lower flammability or explosive limits 0.6 - 8.5 Vol-% Vapour pressure Not available. Vapour density Not available. Relative density Not available. Solubility(ies) Immiscible.

Revision: 6 Page: 4/7 Date: April 2014-04-25





Certificate Number 768 ISO 9001

AC-90 Multipurpose Lubricant

Partition coefficient: n-octanol/water Not available.

Auto-ignition temperature The product is not self-igniting.

Ignition temperature 240°C
Decomposition Temperature Not available.
Viscosity Not available.

Explosive properties Pressurised container: May burst if heated.

Oxidising properties Not oxidising.

9.2 Other information None.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity Stable under normal conditions.
 10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Reacts violently with - Strong oxidising agents.

10.4 Conditions to avoid Heat and direct sunlight. Do not mix with other chemicals.

10.5 Incompatible materials Oxidizing agent, Reducing agent.

10.6 Hazardous Decomposition Product(s)

This product may give rise to hazardous fumes in a fire.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.1 Mixtures

Acute toxicity

Inhalation STOT SE 3; May cause drowsiness or dizziness.

Irritation Repeated exposure may cause skin dryness or cracking.

Corrosivity Not classified.

SensitisationIt is not a skin sensitiser.Repeated dose toxicityNone anticipated.

Carcinogenicity No evidence of carcinogenicity. No components are listed as a

carcinogens or suspected carcinogens.

Mutagenicity There is no evidence of mutagenic potential.

Toxicity for reproduction None anticipated.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity Aquatic Chronic 3; Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability This product is readily biodegradable in soil.

12.3 Bioaccumulative potential No information available.

12.4 Mobility in soil The product is predicted to have low mobility in soil.

12.5 Results of PBT and vPvB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Recycle only completely emptied packaging. Containers must not be

punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility.

13.2 Additional Information Disposal should be in accordance with local, state or national

legislation. Do not allow into any sewer on the ground, or into any

body of water.

Revision: 6 Page: 5/7 Date: April 2014-04-25



AC-90 Multipurpose Lubricant

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number UN 1950

14.2 UN proper shipping name Limited quantity provisions and exceptions apply to aerosol products

in transit.

ADR/RID/ADN/IMDG AEROSOLS.

ICAO/IATA AEROSOLS, FLAMMABLE.

14.3 Transport hazard class(es)

ADR/RID/ADN 2
IMDG/ICAO/IATA 2.1
Packing Group No

14.5 Environmental hazards Not classified as a Marine Pollutant.

1.6 Special precautions for user None

14.7 Transport in bulk according to Annex II of Not applicable.

MARPOL73/78 and the IBC Code

Additional Information
IMDG Code EmS: F-D, S-U

Tunnel Restriction Code D

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

regulations/legislation specific for the substance or

mixture

14.8

15.1.1 EU regulations

Authorisations and/or restrictions on use

Candidate List of Substances of Very High Concern for All chemicals are not listed.

Authorisation

REACH: ANNEX XIV LIST OF SUBSTANCES All chemicals are not listed.

SUBJECT TO AUTHORISATION

REACH: ANNEX XVII RESTRICTIONS ON THE All chemicals are not listed.

MANUFACTURE, PLACING ON THE MARKET

AND USE OF CERTAIN DANGEROUS

SUBSTANCES, PREPARATIONS AND ARTICLES

Community Rolling Action Plan (CoRAP); All chemicals are not listed.

Draft 04/11/2013

 15.1.2
 National regulations
 None known.

 15.2
 Chemical Safety Assessment
 Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

List contains all hazards, precautions and hazard pictograms may/may not be applicable to this product.

LEGEND

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
DNEL Derived No Effect Level
DNEC Predicted No Effect Concept

PNEC Predicted No Effect Concentration
PBT Persistent, Bioaccumulative and Toxic
vPvB very Persistent and very Bioaccumulative

Aerosol 1 Aerosol Category 1

Asp. Tox. 1 Aspiration hazard Category 1 Flam. Gas 1 Flammable gas Category 1 Flam. Liq. 3 Flammable Liquid Category 3

STOT SE 3 Specific target organ toxicity — single exposure Category 3

Revision: 6 Page: 6/7 Date: April 2014-04-25





AC-90 Multipurpose Lubricant

Aquatic Chronic 3 Hazardous to the aquatic environment Category 3

Press. Gas Gases under pressure

Hazard statement(s) and Precautionary statement(s)

H220 Extremely flammable gas. H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking.

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

Hazard pictogram(s) and Hazard Symbol

GHS02 GHS04







Disclaimers

GHS07

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Action Can Ltd. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Action Can Ltd. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.

Revision: 6 Page: 7/7 Date: April 2014-04-25