# **MSDS ATTACHMENT**

# PLEASE ATTACH THIS COMPLETED SHEET TO THE MSDS FOR:

PRODUCT:

CRC 3030 Extreme Duty Silicone

DATE:

(MSDS date)

30/12/2020

1. Manufacturer/Supplier:

**PPS Industries Limited** 

86 Hugo Johnston Drive, Auckland

New Zealand

P.O.Box 12823, Penrose, Auckland 1642

Phone: 64 9 579-1001 Facsimile: 64 9 579-9497

Emergency Phone: 0800 657-894 Website: www.ppsindustries.co.nz

**Emergency Information:** 

National Poison Centre

0800 764-766

Chemcall 24/7 Emergency Response Service :

0800 243-622

13. Disposal Considerations :

**Product** 

Recommendation - Consult local or national regulations to ensure proper disposal.

**Packaging** 

Disposal must be made according to official regulations.

16. Other Information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other

product or process, is the responsibility of the user.



# CRC 3030 Extreme Duty Silicone (Aerosol) (NZ) CRC Industries (CRC Industries New Zealand)

Chemwatch: 4552-29 Version No: 10.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 4

Issue Date: 30/12/2020 Print Date: 18/04/2024 S.GHS.NZL.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	CRC 3030 Extreme Duty Silicone (Aerosol) (NZ)
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available
Relevant identified uses of Relevant identified uses	the substance or mixture and uses advised against  Lubricant.  Application is by spray atomisation from a hand held aerosol pack  Use according to manufacturer's directions.

# Details of the manufacturer or supplier of the safety data sheet

Details of the manufacture	To supplied of the safety data sheet
Registered company name	CRC Industries (CRC Industries New Zealand)
Address	10 Highbrook Drive East Tamaki Auckland New Zealand
Telephone	+64 9 272 2700
Fax	+64 9 274 9696
Website	www.crc.co.nz
Email	info.nz@crc.co.nz

# Emergency telephone number

Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112
Other emergency telephone numbers	111 (NZ Emergency Services)	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

# **SECTION 2 Hazards identification**

### Classification of the substance or mixture

Classification <sup>[1]</sup>	Aerosols Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A

Signal word

# Hazard statement(s)

H222 Extremely flammable aerosol.

# Precautionary statement(s) Prevention

Not Applicable

# Precautionary statement(s) Response

Not Applicable

# Precautionary statement(s) Storage

Not Applicable

# Precautionary statement(s) Disposal

Not Applicable

# **SECTION 3 Composition / information on ingredients**

### **Substances**

See section below for composition of Mixtures

### **Mixtures**

CAS No	%[weight]	Name
Not Available	30-60	aliphatic hydrocarbon
Not Available	1-10	silicone oligomer
68476-85-7.	10-30	LPG (liquefied petroleum gas)
Legend:		ch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No Classification drawn from C&L * EU IOELVs available

# **SECTION 4 First aid measures**

### Description of first aid measures

•	
Eye Contact	<ul> <li>If aerosols come in contact with the eyes:</li> <li>Immediately hold the eyelids apart and flush the eye with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If solids or aerosol mists are deposited upon the skin:  Flush skin and hair with running water (and soap if available).  Remove any adhering solids with industrial skin cleansing cream.  DO NOT use solvents.  Seek medical attention in the event of irritation.
Inhalation	<ul> <li>If aerosols, fumes or combustion products are inhaled:</li> <li>Remove to fresh air.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>
Ingestion	<ul> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> <li>Not considered a normal route of entry.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

• Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.

- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen.
  Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous
  lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves
  clearance
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

Treat symptomatically.

### **SECTION 5 Firefighting measures**

### Extinguishing media

### SMALL FIRE:

Water spray, dry chemical or CO2

### LARGE FIRE:

Water spray or fog.

## Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
result

### Advice for firefighters

# Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- · Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Severe explosion hazard, in the form of vapour, when exposed to flame or spark.

# Fire/Explosion Hazard

Combustion products include: carbon monoxide (CO)

carbon dioxide (CO2)

silicon dioxide (SiO2)

other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

### **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

# Minor Spills

- · Clean up all spills immediately.
- · Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Remove leaking cylinders to a safe place if possible.
- · Release pressure under safe, controlled conditions by opening the valve.
- DO NOT exert excessive pressure on valve; DO NOTattempt to operate damaged valve.
- Major Spills Clear area of personnel and move upwind.
  - Alert Fire Brigade and tell them location and nature of hazard.
  - May be violently or explosively reactive.
  - Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

### Precautions for safe handling

Safe handling

Containers, even those that have been emptied, may contain explosive vapours.

- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- · Keep containers securely sealed.

### Conditions for safe storage, including any incompatibilities

Suitable container

Other information

- · Aerosol dispenser.
- Check that containers are clearly labelled.
- Storage incompatibility
- · Avoid reaction with oxidising agents

# SECTION 8 Exposure controls / personal protection

### Control parameters

Occupational Exposure Limits (OEL)

### **INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	LPG (liquefied petroleum gas)	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available
Emergency Limits						
Ingredient	TEEL-1	TEEL-2		TEEL-3		
LPG (liquefied petroleum gas)	65,000 ppm	2.30E+05 ppm		4.00E+05	ppm	

# Ingredient Original IDLH Revised IDLH

LPG (liquefied petroleum gas)

2,000 ppm

Not Available

### **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment

Eye and face protection











- No special equipment for minor exposure i.e. when handling small quantities.
- ► OTHERWISE: For potentially moderate or heavy exposures:
- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

# Hands/feet protection

- Personal hygiene is a key element of effective hand care.
- No special equipment needed when handling small quantities,
   OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.
- For potentially heavy exposures:
- Wear chemical protective gloves, eg. PVC. and safety footwear.

### **Body protection**

See Other protection below

# Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.

- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

No special equipment needed when handling small quantities.

# Other protection

# OTHERWISE: • Overalls.

- Skin cleansing cream.
- ▶ Eyewash unit.

# Respiratory protection

Type AX Filter of sufficient capacity, (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2	AX-PAPR-2 ^
up to 10 x ES		AX-3	
10+ x ES	-	Air-line**	1-

<sup>\* -</sup> Continuous Flow; \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- · Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

A clear water white flammable liquid with a solvent odour; not miscible with water.

### **SECTION 9 Physical and chemical properties**

# Information on basic physical and chemical properties

Appearance	Supplied as an aerosol pack. Contents ur	nder PRESSURE. Contains highly flammable hydronic	ocarbon propella
Physical state	Liquid	Relative density (Water = 1)	0.927
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	550
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	67	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	-81 (propellant)	Taste	Not Available
Evaporation rate	15 BuAc=1	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	10.7	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.3	Volatile Component (%vol)	97
Vapour pressure (kPa)	13.3 @ 20 C	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available

<sup>^ -</sup> Full-face

Reactivity

See section 7

Chemical stability

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Possibility of hazardous reactions

See section 7

Conditions to avoid Incompatible materials See section 7

Hazardous decomposition

See section 7

products

See section 5

### **SECTION 11 Toxicological information**

Inhaled

### Information on toxicological effects

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo,

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with

headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings

may result in respiratory depression and may be fatal. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal. Exposure to hydrocarbons may result in irregularity of heart beat. Symptoms of moderate poisoning may include dizziness, headache, nausea.

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may Ingestion result. (ICSC13733)

Accidental ingestion of the material may be damaging to the health of the individual.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

**Skin Contact** Spray mist may produce discomfort

Open cuts, abraded or irritated skin should not be exposed to this material

Eye Not considered to be a risk because of the extreme volatility of the gas.

Main route of exposure to the gas in the workplace is by inhalation.

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

CRC 3030 Extreme Duty Silicone (Aerosol) (NZ)

Chronic

TOXICITY IRRITATION Not Available Not Available

TOXICITY IRRITATION LPG (liquefied petroleum

gas) Inhalation (Rat) LC50: 658 mg/l4h<sup>[2]</sup> Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

LPG (LIQUEFIED PETROLEUM GAS)

Mutagenicity

No significant acute toxicological data identified in literature search, inhalation of the gas

**Acute Toxicity** × Carcinogenicity × Skin Irritation/Corrosion Reproductivity Serious Eye STOT - Single Exposure Damage/Irritation Respiratory or Skin × STOT - Repeated Exposure sensitisation

> Leaend: — Data either not available or does not fill the criteria for classification

> > – Data available to make classification

**Aspiration Hazard** 

### **Toxicity**

CRC 3030 Extreme Duty Silicone (Aerosol) (NZ) Endpoint Test Duration (hr) Species

Value

Source

Not Not Available Available

Not Available

Not Available

Not Not Available Available

LPG (liquefied petroleum

gas)

Not

Available

**Endpoint** Test Duration (hr) Not Available

**Species** 

Value Not

Available

Source Not

Available

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Hydrocarbons: log Kow 1. BCF~10.

For Aromatics: log Kow 2-3.

BCF 20-200.

Drinking Water Standards: hydrocarbon total: 10 ug/I (UK max.).

DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient

Persistence: Water/Soil

Persistence: Air

No Data available for all ingredients

No Data available for all ingredients

Bioaccumulative potential

Ingredient

Bioaccumulation

No Data available for all ingredients

Mobility in soil

Ingredient

Mobility

No Data available for all ingredients

# **SECTION 13 Disposal considerations**

### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

### Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- · Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

# **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

# **SECTION 14 Transport information**



### **Marine Pollutant**

NO

HAZCHEM

Not Applicable

# Land transport (UN)

14.1. UN number or ID number

1950

14.2. UN proper shipping name

**AEROSOLS** 

14.3. Transport hazard class(es)

Class 2.1

Subsidiary Hazard

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazard

Not Applicable

14.6. Special precautions for user

Special provisions 63; 190; 277; 327; 344; 381

Limited quantity

1000ml

# Air transport (ICAO-IATA / DGR)

14.1. UN number	1950	
14.2. UN proper shipping name	Aerosols, flammable	
14.3. Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subsidiary Hazard ERG Code	2.1 Not Applicable 10L
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	

14.6. Special precautions for user

Special provisions A145 A167 A802
Cargo Only Packing Instructions 203
Cargo Only Maximum Qty / Pack 150 kg
Passenger and Cargo Packing Instructions 203
Passenger and Cargo Maximum Qty / Pack 75 kg
Passenger and Cargo Limited Quantity Packing Instructions Y203
Passenger and Cargo Limited Maximum Qty / Pack 30 kg G

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950		
14.2. UN proper shipping name	AEROSOLS		
14.3. Transport hazard class(es)	IMDG Class 2.1  IMDG Subsidiary Hazard Not Applicable		
14.4. Packing group 14.5 Environmental hazard	Not Applicable Not Applicable		
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	F-D , S-U 63 190 277 327 344 381 959 1000 ml	

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name

Group

LPG (liquefied petroleum

gas)

Not Available

### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name

Ship Type

LPG (liquefied petroleum

Lr & (liquelled petroledi)

Not Available

gas)

# **SECTION 15 Regulatory information**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

**HSR Number** 

**Group Standard** 

HSR002515

Aerosols (Flammable) Group Standard 2017

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

### LPG (liquefied petroleum gas) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

### **Additional Regulatory Information**

Not Applicable

## **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard	Clace
Hazaru	Class

# **Quantity (Closed Containers)**

Quantity (Open Containers)

2.1.2A

3 000 L (aggregate water capacity)

3 000 L (aggregate water capacity)

# **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class	of	substan	се
	-		

Quantities

Not Applicable

Not Applicable

Refer Group Standards for further information

# Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

# **Tracking Requirements**

Not Applicable

# **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (LPG (liquefied petroleum gas))
China - IECSC	Yes

National Inventory	Status
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

### **SECTION 16 Other information**

Revision Date	30/12/2020
Initial Date	12/11/2001

### **SDS Version Summary**

Version	Date of Update	Sections Updated
9.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
10.1	30/12/2020	Classification change due to full database hazard calculation/update.

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

# Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act

- TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.