

Hydrolubric® No. 2

Water Soluble Hydraulic Fluid.

DESCRIPTION

Hydrolubric No. 2 is a soluble oil concentrate for water hydraulics. When used as recommended, it will provide lubricating and rust preventive characteristics for internal working surfaces to provide efficient and maintain production at top speed.

Unit or Independent Self-contained Systems

Years of field experience in equipment designed for use with high water content fluids has shown that 5% solutions of Hydrolubric No. 2 in tap water will perform well at rated outputs.

Central Water Systems

Hydraulic presses and central accumulator hydraulic systems designed for water operation, using constant volume reciprocating plunger or multi-stage centrifugal pumps, have demonstrated their suitability for use with Hydrolubric No. 2 at concentrations of 2% to 5%. Hydrolubric No. 2 is completely compatible with conventional soluble oils. It can be added directly to a soluble oil system provided the systems are relatively free of deposits and/or biological growth.

FEATURES

- Cost effective
- Low maintenance
- Fire resistant fluid

TYPICAL VALUES

	Brown Oil	White Opaque
Appearance	Brown Oil	White Opaque
Viscosity @ 40°C	22 cSt	0.80 cSt
pH	9.6	9.4
Freezing Point, °C-	1.0	0
Density, kg/L	0.915	1.05

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D001A0200



Houghton Australia Pty Ltd
287 Wickham Road
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642
Fax: +61 1300 736 234
info@houghton.com.au
www.houghton.com.au

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

Hydrolubric® No. 2

Water Soluble Hydraulic Fluid.

REFERENCES

Used widely in steel mill application's

HOW TO USE

The recommended usage concentration of Hydrolubric No. 2 is normally used at a concentration of 2% - 5% in tap water. In this concentration range, the polarity of the synthetic components serves to provide a film on metal surfaces that effectively reduces friction coefficients and provides protection against aqueous corrosion. This may be customised to suit individual needs or solutions, which may vary from time.

SHELF LIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **PRODUCT** is a minimum of Twelve (12) months, unless otherwise specified.

PRODUCT is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

RELATED PRODUCTS

- CUT-MAX: Straight cutting oils
- HOCUT: Water miscible metalworking fluids
- DROMUS: Soluble metalworking fluids
- ADRANA: Micro-emulsion metalworking fluids
- METALINA: Synthetic metalworking fluids
- HOUGHTO-GRIND: Straight and water miscible grinding fluids
- HOUGHTO-DRAW: Straight and water miscible drawing stamping and forming fluids.
- CINDOL: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- CERFA-KLEEN: Water miscible cleaning fluids
- RUST VETO: Straight and water miscible rust preventive fluids.

FLUID MAINTENANCE

These can be routinely performed and organised through Houghton's Customer Service laboratory, please contact your sales representative for further information about this service.

Houghton recommends that periodic checks of **Hydrolubric No 2** should be carried out .

01 July 2011 Version 1.0, Code: D001A0200



HOUGHTON™

Houghton Australia Pty Ltd
287 Wickham Road
Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642
Fax: +61 1300 736 234
info@houghton.com.au
www.houghton.com.au

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.