

# MSDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE MSDS FOR :

PRODUCT :

LOCTITE 290 Threadlocker

DATE :

(MSDS date)

27.05.2019

**1. Manufacturer/Supplier :** PPS Industries Limited  
86 Hugo Johnston Drive, Auckland  
New Zealand  
P.O.Box 12823, Penrose, Auckland 1642  
Phone : 64 9 579-1001  
Facsimile : 64 9 579-9497  
Emergency Phone : 0800 657-894  
Website: www.ppsindustries.co.nz

**Emergency Information :** National Poison Centre 0800 764-766  
Chemcall 24/7 Emergency Response Service : 0800 243-622

**13. Disposal Considerations :** Product  
Recommendation - Consult local or national regulations to ensure proper disposal.

Packaging  
Disposal must be made according to official regulations.

**16. Other Information :** Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.



## Safety Data Sheet

Page 1 of 8

LOCTITE 290 WICKING GRADE THREADLOCKER

SDS No. : 153486

V001.1

Revision: 27.05.2019

printing date: 01.10.2023

### SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product name:** LOCTITE 290 WICKING GRADE THREADLOCKER

**Intended use:** Anaerobic Sealant

**Supplier:**

Henkel New Zealand Ltd  
2 Allens Rd  
Auckland, 2013  
New Zealand

Phone: +64 (9) 272-6710

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

### SECTION 2 HAZARDS IDENTIFICATION

**Classification of the substance or mixture**

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.  
Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

**HSNO Classification:**

6.4A Class 6 - Toxicity, Subclass 6.4 - Eye irritant, Hazard Classification A  
Class 6 - Toxicity, Subclass 6.1 - Acutely toxic, Hazard Classification E  
Class 9 - Ecotoxicity, Subclass 9.1 - Aquatic, Hazard Classification C

**GHS Classification:**

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Serious eye irritation	Category 2A	
Target Organ Systemic Toxicant - Single exposure	Category 3	respiratory tract irritation
Acute hazards to the aquatic environment	Category 3	
Chronic hazards to the aquatic environment	Category 3	

**Hazard pictogram:**



**Signal word:**

Warning

<b>Hazard statement(s):</b>	H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary Statement(s):</b>	
<b>Prevention:</b>	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear eye protection/face protection.
<b>Response:</b>	P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.
<b>Storage:</b>	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
<b>Disposal:</b>	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

**SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS**

**General chemical description:** Mixture  
**Type of preparation:** Anaerobic Sealant

**Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
Cumene hydroperoxide	80-15-9	1- < 3 %
Methyl methacrylate	80-62-6	< 1 %
non hazardous ingredients~		60- < 100 %

**SECTION 4 FIRST AID MEASURES**

<b>Ingestion:</b>	Rinse mouth, do not induce vomiting, consult a doctor.
<b>Skin:</b>	Rinse with running water and soap. If symptoms develop and persist, get medical attention.
<b>Eyes:</b>	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.
<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>First Aid facilities:</b>	Normal washroom facilities

**SECTION 5. FIRE FIGHTING MEASURES**

<b>Suitable extinguishing media:</b>	Carbon dioxide, foam, powder
<b>Improper extinguishing media:</b>	None known

**Decomposition products in case of fire::** Oxides of carbon.

**Particular danger in case of fire::** In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released. In case of fire, keep containers cool with water spray.

**Special protective equipment for fire-fighters:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Avoid skin and eye contact.  
Ensure adequate ventilation.  
See advice in section 8

**Environmental precautions:** Do not let product enter drains.

**Clean-up methods:** For small spills wipe up with paper towel and place in container for disposal.  
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**SECTION 7. HANDLING AND STORAGE**

**Precautions for safe handling:** Use only in well-ventilated areas.  
See advice in section 8  
Wear suitable protective clothing, safety glasses and gloves.

**Conditions for safe storage:** Ensure good ventilation/extraction.  
Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Workplace exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
METHYL METHACRYLATE 80-62-6		50	208	-	-	-
METHYL METHACRYLATE		-	-	-	100	416

**Engineering controls:** Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Eye protection:** Wear protective glasses.

**Skin protection:** Wear suitable protective clothing.  
Use of Butyl or Nitrile Rubber gloves is recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

**Respiratory protection:** Use only in well-ventilated areas.  
If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** green  
liquid  
**Odor:** mild  
**Specific gravity:** 1.07  
**Boiling point:** > 150 °C (> 302 °F)  
**Flash point:** > 93.3 °C (> 199.94 °F)  
(Tagliabue closed cup)  
**Vapor pressure:** < 5 mm hg  
(; 27.0 °C (80.6 °F))  
**Density:** 1.07 g/cm<sup>3</sup>  
**VOC content:** < 3 %  
(2010/75/EC)

**SECTION 10. STABILITY AND REACTIVITY**

**Conditions to avoid:** Keep away from heat, ignition sources and incompatible materials.

**Incompatible materials:** Reaction with strong acids.  
Reacts with strong oxidants.  
Strong alkalis.  
Strong reducing agents.

**Hazardous decomposition products:** Irritating and toxic gases or fumes may be released during a fire.  
Oxides of carbon.

**Hazardous polymerization:** None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Health Effects:**  
**Ingestion:** Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.  
**Skin:** May cause mild skin irritation.  
**Eyes:** Vapors irritate the eyes. Contact with liquid or mist will irritate the eyes.  
**Inhalation:** Inhalation of vapors may cause moderate to severe respiratory tract irritation.

**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LD50	382 mg/kg	oral		rat	other guideline: other guideline: Expert judgement
	LD50	530 - 1,060 mg/kg	dermal		rat	
Methyl methacrylate 80-62-6	Acute toxicity estimate (ATE)	1,100 mg/kg	dermal	4 h	rat	not specified not specified not specified
	LD50	9,400 mg/kg	oral		rat	
	LC50	29.8 mg/l	inhalation		rat	
	LD50	> 5,000 mg/kg	dermal		rabbit	

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
Methyl methacrylate 80-62-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
Methyl methacrylate 80-62-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified

**Repeated dose toxicity:**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified
Methyl methacrylate 80-62-6	LOAEL=2000 ppm	inhalation	14 weeks 6 hrs/day, 5 days/wk	mouse	Dose Range Finding Study
Methyl methacrylate 80-62-6	NOAEL=1000 ppm	inhalation	14 weeks 6 hrs/day, 5 days/wk	mouse	Dose Range Finding Study

**SECTION 12. ECOLOGICAL INFORMATION**

**General ecological information:**

Components of this product are hazardous to aquatic life., Do not empty into drains / surface water / ground water., Cured Loctite products are typical polymers and do not pose any immediate environmental hazards.

**Toxicity:**

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test) not specified
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		
Methyl methacrylate 80-62-6	LC50	350 mg/l	Fish		Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl methacrylate 80-62-6	EC50	69 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl methacrylate 80-62-6	EC50	170 mg/l	Algae	4 d	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methyl methacrylate 80-62-6	NOEC	100 mg/l	Algae	4 d	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methyl methacrylate 80-62-6	EC0	100 mg/l	Bacteria	30 min		not specified

**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methyl methacrylate 80-62-6	readily biodegradable	acrobic	95 %	EU Method C.4-B (Determination of the "Ready" Biodegradability Modified OECD Screening Test)

**Bioaccumulative potential / Mobility in soil:**

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Cumene hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration; Flow-through Fish Test)
Cumene hydroperoxide 80-15-9	2.16					not specified
Methyl methacrylate 80-62-6	1.38					not specified

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Waste disposal of product:**

Dispose of as hazardous waste in compliance with local and national regulations.  
Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

**Disposal for uncleaned package:** Dispose of in accordance with local and national regulations.

**SECTION 14. TRANSPORT INFORMATION**

**Dangerous Goods information:**

Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

**Marine transport IMDG:**

Not dangerous goods

**Air transport IATA:**

Not dangerous goods

**SECTION 15. REGULATORY INFORMATION**

**New Zealand regulatory information:**

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

**HSNO Approval Number:** Group standard HSR002670

**NZIoC:** Compliant for NZIOC

**SECTION 16. OTHER INFORMATION**

**Abbreviations/acronyms:** STEL - Short term exposure limit  
TWA - Time weighted average  
IMDG: International Maritime Dangerous Goods code  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 2,3,8



**Date of previous issue:** 30.06.2014

**Disclaimer:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.