MSDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE MSDS FOR:

PRODUCT:

Loctite 222 Threadlocker

DATE:

(MSDS date)

11.01.2019

1. Manufacturer/Supplier:

PPS Industries Limited

86 Hugo Johnston Drive, Auckland

New Zealand

P.O.Box 12823, Penrose, Auckland 1642

Phone: 64 9 579-1001 Facsimile: 64 9 579-9497

Emergency Phone: 0800 657-894 Website: www.ppsindustries.co.nz

Emergency Information:

National Poison Centre

0800 764-766

Chemcall 24/7 Emergency Response Service: 0800 243-622

13. Disposal Considerations:

Product

Recommendation - Consult local or national regulations to ensure proper disposal.

Packaging

Disposal must be made according to official regulations.

16. Other Information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other

product or process, is the responsibility of the user.



Safety Data Sheet

Page 1 of 8

SDS No.: 153481

V001.1

Revision: 11.01.2019 printing date: 22.07.2023

IDENTIFICATION OF THE MATERIAL AND SUPPLIER **SECTION 1**

Product name:

LOCTITE 222MS known as Loctite 222 Threadlocker

Intended use:

Anaerobic Sealant

Supplier:

Henkel New Zealand Ltd 2 Allens Rd Auckland, 2013 New Zealand

Phone:

+64 (9) 272-6710

LOCTITE 222MS known as Loctite 222 Threadlocker

Emergency information:

24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001. Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

HSNO Classification:

6.4A Class 6 - Toxicity, Subclass 6.4 - Eye irritant, Hazard Classification A Class 9 - Ecotoxicity, Subclass 9.1 - Aquatic, Hazard Classification C

GHS Classification:

Hazard Class

Hazard Category

Target organ

Serious eye irritation Target Organ Systemic Toxicant -

Category 2A Category 3

respiratory tract irritation

Single exposure

Acute hazards to the aquatic

Category 3

environment Chronic hazards to the aquatic

environment

Category 3

Hazard pictogram:

Signal word:

Warning

SDS No.: 153481 V001.1

LOCTITE 222MS known as Loctite 222 Threadlocker

Hazard statement(s):

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response:

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description:

Mixture

Type of preparation:

Methacrylate resin based threadlocker

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Cumene hydroperoxide	80-15-9	1-< 3 %
Propane-1,2-diol	57-55-6	< 10 %
non hazardous ingredients~		60-<100 %

SECTION 4 FIRST AID MEASURES

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

Skin:

Wash skin with water

In case of adverse health effects seek medical advice.

Eyes:

Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical

attention.

Inhalation:

Should not be a problem as product is of low volatility. However, if feeling unwell

remove patient to fresh air.

First Aid facilities:

Eye wash

Normal washroom facilities

V001.1

LOCTITE 222MS known as Loctite 222 Threadlocker

SECTI

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

Foam, dry chemical or carbon dioxide.

Decomposition products in case of

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

fire::

Oxides of sulfur.

Particular danger in case of fire::

None

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with eyes, skin and clothing.

Avoid breathing vapors or mists of this product.

Wash thoroughly after handling. Use only with adequate ventilation.

See advice in section 8

Conditions for safe storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep

container tightly closed until ready for use. Store in original container until ready to use.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure standards:

Ingredient [Regulated		TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
substance]	exposure					
PROPANE-1,2-DIOL, PARTICULATES ONLY 57-55-6	Particulate.		10			
PROPANE-1,2-DIOL, VAPOUR & PARTICULATES	Vapor and particulates.	150	474			

Page 4 of 8

SDS No.: 153481

V001.1

LOCTITE 222MS known as Loctite 222 Threadlocker

Engineering controls:

No specific ventilation requirements noted, but forced ventilation may still be required if

concentrations exceed occupational exposure limits.

Eye protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

Neoprene gloves.

Butyl rubber gloves.

Natural rubber gloves.

Respiratory protection:

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Purple

Odor:

Liquid mild

Specific gravity:

1.05

Boiling point:

> 149.0 °C (> 300.2 °F) > 93.3 °C (> 199.94 °F)

Flash point:

(Tagliabue closed cup)

Density:

1.0800 g/cm3

Solubility in water:

Slightly soluble

SECTION 10.

STABILITY AND REACTIVITY

Conditions to avoid:

See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

Incompatible materials:

Strong alkalis. Reducing agents. Strong oxidizing agents.

Acids.

Hazardous decomposition

Irritating and toxic gases or fumes may be released during a fire.

products:

Oxides of sulfur. Oxides of nitrogen. Oxides of carbon.

Hazardous polymerization:

Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

SDS No.: 153481 V001.1

LOCTITE 222MS known as Loctite 222 Threadlocker

Health Effects:

Ingestion:

May cause mild gastrointestinal irritation with nausea, vomiting, diarrhea and abdominal pain.

Skin:

May cause mild skin irritation.

Eyes: Inhalation: Contact with eyes will cause irritation.
May cause respiratory tract irritation.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	not specified
80-15-9	LD50	1,200 - 1,520				not specified
		mg/kg	dermal	ļ.		
Propane-1,2-diol	LD50	22,000 mg/kg	oral		rat	not specified
57-55-6	LC50	> 317.042 mg/l	inhalation	2 h	rabbit	not specified
ì	LD50	> 2,000 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Propane-1,2-diol	not irritating	4 h	rabbit	OECD Guideline 404 (Acute
57-55-6				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Propane-1,2-diol	not irritating		rabbit	OECD Guideline 405 (Acute
57-55-6	_			Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Propane-1,2-diol 57-55-6	not sensitising	Guinea pig maximisat ion test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide negative 80-15-9		dermal		mouse	not specified
Propane-1,2-diol 57-55-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	without with and without		Ames Test OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
57-55-6 negative intraperit		oral: gavage intraperitoneal oral: gavage		rat mouse rat	not specified not specified not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9	·	inhalation: aerosol	6 h/d5 d/w	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1,700 mg/kg	oral: feed	2 yearsdaily	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1000 mg/m3	inhalation	90 d6 h/d, 5 d/w	rat	not specified

SECTION 12.

ECOLOGICAL INFORMATION

General ecological information:

Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
Propane-1,2-diol 57-55-6	LC50	> 10,000 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Propane-1,2-diol 57-55-6	EC50	18,340 mg/l	Daphnia	48 h	Ceriodaphnia dubia	other guideline:
Propane-1,2-diol 57-55-6	EC50	24,200 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	NOEC	15,000 mg/l	Algae	14 d	Pseudokirchneriella subcapitata	/
Propane-1,2-diol 57-55-6	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Propane-1,2-diol 57-55-6	not inherently biodegradable	aerobic	60 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Propane-1,2-diol 57-55-6	readily biodegradable	aerobic	> 70 %	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Page 7 of 8

SDS No.: 153481

V001.1

LOCTITE 222MS known as Loctite 222 Threadlocker

Cumene hydroperoxide 80-15-9		9.1	calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2.16				not specified
Propane-1,2-diol 57-55-6	-1.07			20.5 °C	EU Method A.8 (Partition Coefficient)

SECTION 13.

DISPOSAL CONSIDERATIONS

Waste disposal of product:

Dispose of in accordance with local and national regulations.

Disposal for uncleaned package:

After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

SECTION 14.

TRANSPORT INFORMATION

Dangerous Goods information:

Not Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

SECTION 15.

REGULATORY INFORMATION

New Zealand regulatory information:

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

HSNO Approval Number:

Group standard HSR002670

Site and Storage:

Refer to the site and storage requirements for this Group Standard.

NZIoC:

The hazardous components of this product are listed on the New Zealand Inventory of

chemicals (NZIoC).

LOCTITE 222MS known as Loctite 222 Threadlocker

SECTION 16.

OTHER INFORMATION

Abbreviations/acronyms:

HSNO - Hazardous Substances and New Organisms

TWA - Time weighted average STEL - Short term exposure limit

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

Reason for issue:

Reviewed SDS. Reissued with new date, involved chapters: 1-16

Date of previous issue:

03.02.2014

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.