

# MSDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE MSDS FOR :

PRODUCT :

Loctite 401

DATE :

(MSDS date)

29.08.2022

**1. Manufacturer/Supplier :**

PPS Industries Limited  
86 Hugo Johnston Drive, Auckland  
New Zealand  
P.O.Box 12823, Penrose, Auckland 1642  
Phone : 64 9 579-1001  
Facsimile : 64 9 579-9497  
Emergency Phone : 0800 657-894  
Website: www.ppsindustries.co.nz

**Emergency Information :**

National Poison Centre 0800 764-766  
Chemcall 24/7 Emergency Response Service : 0800 243-622

**13. Disposal Considerations :**

**Product**

Recommendation - Consult local or national regulations to ensure proper disposal.

**Packaging**

Disposal must be made according to official regulations.

**16. Other Information :**

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.



## Safety Data Sheet

Page 1 of 7

LOCTITE 401

SDS No. : 624092

V001.0

Revision: 29.08.2022

printing date: 07.03.2023

### SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product name:** LOCTITE 401

**Intended use:** Adhesive

**Supplier:**  
Henkel New Zealand Ltd  
2 Allens Rd  
Auckland, 2013  
New Zealand  
Phone: +64 (9) 272-6710

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

### SECTION 2 HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

#### GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Target organ</u>
Flammable liquids	Category 4	
Skin irritation	Category 2	
Serious eye irritation	Category 2A	
Target Organ Systemic Toxicant - Single exposure	Category 3	respiratory tract irritation

#### Hazard pictogram:



#### Signal word:

Warning

**Hazard statement(s):** H227 Combustible liquid.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

**Precautionary Statement(s):**

**Prevention:** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist/vapours.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** P302+P352 IF ON SKIN: Wash with plenty of water.  
P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

**SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS**

**General chemical description:** Mixture

**Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
Ethyl 2-cyanoacrylate	7085-85-0	90- <= 100 %

**SECTION 4 FIRST AID MEASURES**

**Ingestion:** Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.

**Skin:** Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.

<b>Eyes:</b>	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.
<b>Inhalation:</b>	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
<b>First Aid facilities:</b>	Eye wash and safety shower Normal washroom facilities
<b>Medical attention and special treatment:</b>	Treat symptomatically.

#### SECTION 5. FIRE FIGHTING MEASURES

<b>Suitable extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Decomposition products in case of fire:</b>	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.
<b>Particular danger in case of fire:</b>	None
<b>Special protective equipment for fire-fighters:</b>	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	Ventilate area. Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

#### SECTION 7. HANDLING AND STORAGE

<b>Precautions for safe handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.
<b>Conditions for safe storage:</b>	Refer to Technical Data Sheet

#### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Workplace exposure standards:</b>	
<b>Biological Exposure Indices:</b>	None

<b>Eye protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
<b>Skin protection:</b>	Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.
<b>Respiratory protection:</b>	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	colourless to yellowish liquid
<b>Odor:</b>	Sharp
<b>pH:</b>	Not applicable, Product reacts with water.
<b>Melting point / freezing point:</b>	Not applicable, Product is a liquid
<b>Boiling point:</b>	> 149 °C (> 300.2 °F)
<b>Flash point:</b>	80 - 93 °C (176 - 199.4 °F)
<b>Flammability (solid, gas):</b>	flammable
<b>Vapor pressure:</b> (; 50 °C (122 °F))	< 700 mbar
<b>Density:</b>	1.1 g/cm <sup>3</sup>
<b>Viscosity (dynamic):</b> (Brookfield; Instrument: LVF; 25 °C (77 °F); speed of rotation: 30 min <sup>-1</sup> ; Spindle No: 1; Method: ;; LCT STM 10; Viscosity Brookfield)(Cone and plate; Instrument: Physica MC 100 (or equivalent), Cone CP50-1; 25 °C (77 °F); Shear gradient: 3,000 s <sup>-1</sup> ; Method: ;; LCT STM 740; cone & plate viscosity)	100.0 - 120.0 mPa.s 70.0 - 110.0 mPa.s

## SECTION 10. STABILITY AND REACTIVITY

<b>Conditions to avoid:</b>	Spontaneous polymerization.
<b>Incompatible materials:</b>	Water, amines, alkalis and alcohols.
<b>Hazardous decomposition products:</b>	None

## SECTION 11 TOXICOLOGICAL INFORMATION

**Health Effects:**

**Ingestion:** May cause irritation of the stomach  
**Skin:** Causes skin irritation.  
**Eyes:** Causes serious eye irritation.  
**Inhalation:** May cause respiratory tract irritation.

**Acute toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 5,000 mg/kg	oral		rat	equivalent or similar to OECD Guideline 423 (Acute Oral toxicity) equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
	LD50	> 2,000 mg/kg	dermal		rabbit	

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	slightly irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising	Skin sensitisation	guinea pig	not specified

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**SECTION 12. ECOLOGICAL INFORMATION**

**General ecological information:** Do not empty into drains / surface water / ground water.

**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
------------------------------	--------	----------------------	---------------	--------

Ethyl 2-cyanoacrylate 7085-85-0	not readily biodegradable.	aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
------------------------------------	----------------------------	---------	------	---

**Bioaccumulative potential / Mobility in soil:**

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Ethyl 2-cyanoacrylate 7085-85-0	0.776				22 °C	EU Method A.8 (Partition Coefficient)

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Waste disposal of product:** Dispose of in accordance with local and national regulations.

**Disposal for uncleaned package:** Packaging that cannot be cleaned are to be disposed of in the same manner as the product. After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

**SECTION 14. TRANSPORT INFORMATION**

**Dangerous Goods information:**

**Land Transport:**

Not classified as Dangerous Goods under the Land Transport Rule: Dangerous Goods 2005.

**Marine transport IMDG:**

Not dangerous goods

**Air transport IATA:**

UN no.: 3334  
 Proper shipping name: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)  
 Class or division: 9  
 Packing group: III  
 Packing instructions (passenger): 964  
 Packing instructions (cargo): 964  
 Additional Information IATA:  
 Additional Information IATA: Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.  
 Additional Information IATA: Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

**SECTION 15. REGULATORY INFORMATION**

**New Zealand regulatory information:**

Classified as hazardous under the New Zealand Hazardous Substances and New Organisms Act (HSNO).

**HSNO Approval Number:** HSR002657

**Site and Storage:** Refer to the site and storage requirements for this Group Standard.  
Refer to the HSNO controls for approved hazardous substances.

**NZIoC:** Compliant for NZIOC

---

<b>SECTION 16. OTHER INFORMATION</b>
--------------------------------------

---

**Abbreviations/acronyms:** STEL - Short term exposure limit  
TWA - Time weighted average  
HSNO - Hazardous Substances and New Organisms  
GHS: Globally Harmonized System  
CAS: Chemical Abstracts Service  
IMDG: International Maritime Dangerous Goods code  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

**Reason for issue:** First issue. involved chapters: 1-16

**Disclaimer:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.