

MSDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE MSDS FOR :

PRODUCT :

QUAKER HOUGHTON RUST VETO 377DGHF

DATE :

(MSDS date)

21.09.2019

1. Manufacturer/Supplier :

PPS Industries Limited
86 Hugo Johnston Drive, Auckland
New Zealand
P.O.Box 12823, Penrose, Auckland 1642
Phone : 64 9 579-1001
Facsimile : 64 9 579-9497
Emergency Phone : 0800 657-894
Website: www.ppsindustries.co.nz

Emergency Information :

National Poison Centre : 0800 764-766
Chemcall 24/7 Emergency Response Service : 0800 243-622

13. Disposal Considerations :

Product

Recommendation - Consult local or national regulations to ensure proper disposal.

Packaging

Disposal must be made according to official regulations.

16. Other Information :

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.



SAFETY DATA SHEET

Revision Date 09-21-2019

Version 4

SECTION 1: IDENTIFICATION

Product identifier

Product Code(s) 21337747-M
Product Name RUST VETO 377DGHF

Other means of identification

UN Number UN3082

Recommended use of the chemical and restrictions on use

Recommended Use Rust preventive
Uses advised against Any other purpose.

Suppliers name, address and phone number

Manufacturer, Importer, Supplier

Houghton Australia Pty. Ltd.
287 Wickham Road
Moorabbin, Victoria
Australia, 3189
+61 1300 736 642

Emergency telephone number

For further information, please contact: ProductStewardship@houghtonintl.com

Emergency Telephone 3E Company (+)1 760 476 3960 (Code 333938)
Australia: (+)61 1 800 686 951
Australia (+)61 280 363 166
New Zealand: (+)64 800 451719

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids	Category 4 - (H227)
Aspiration toxicity	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Exclamation mark
Health hazards



Signal word
DANGER

Hazard statements

H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	CAS No	Weight-%
Kerosine (petroleum)	8008-20-6	50% - 100%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	10% - 25%
Barium bis(dinonylnaphthalenesulphonate)	25619-56-1	1% - 2.5%
2-Butoxyethanol	111-76-2	1% - 2.5%

The remaining composition is a mixture of non-classified ingredients or additives below the threshold for disclosure

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General advice	Immediate medical attention is required. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapors/spray.
Inhalation	Move to fresh air. Potential for aspiration if swallowed. Get medical attention immediately if symptoms occur.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
Ingestion	Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. Aspiration hazard if swallowed - can enter lungs and cause damage. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways. Redness. Rash. Itching.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES**Extinguishing media****Suitable Extinguishing Media**

Use CO2, dry chemical, or foam. Cool containers / tanks with water spray. Water spray or fog.

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Flammable Risk of ignition Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke) This material creates a fire hazard because it floats on water Water runoff can cause environmental damage

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

Special protective equipment and precautions for fire fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem emergency action code -3Z.

SECTION 6: ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Keep people away from and upwind of spill/leak. Remove all sources of ignition.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Wear personal protective equipment. Remove all sources of ignition. Do not eat, drink or smoke when using this product. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children.

Recommended Shelf Life

No information available

Incompatible materials

None known based on information supplied.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	Australia	New Zealand	New Zealand - Biological Exposure Indices (BEI)
Kerosine (petroleum)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	
Highly refined base oil (Viscosity >20.5 cSt @40°C)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	
Barium bis(dinonylnaphthalenesulphonate)	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ Ba	
2-Butoxyethanol	TWA: 20 ppm TWA: 96.9 mg/m ³ STEL: 50 ppm STEL: 242 mg/m ³ (s)	TWA: 25 ppm TWA: 121 mg/m ³ (s)	

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields.

Skin and body protection	Wear protective gloves/clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Environmental exposure controls	No information available.
Hygiene measures	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.
Thermal hazards	None under normal use conditions.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Appearance	Dark brown
Odor	Not Determined	Odor threshold	Not Determined
<u>Property</u>	<u>Values</u>		<u>Remarks</u>
pH	Not applicable		
Melting point / freezing point	Not Determined		
Boiling point / boiling range	Not Determined		
Flash point	66 °C / 151 °F		Closed cup
Evaporation rate	Not Determined		
Flammability (solid, gas)	Not Determined		
Flammability Limit in Air			
Upper flammability limit:	Not Determined		
Lower flammability limit:	Not Determined		
Vapor pressure	Not Determined		
Vapor density	Not Determined		
Relative density	0.85		g/cm3 @15°C
Solubility(ies)	Insoluble in water		
Partition coefficient	Not Determined		
Autoignition temperature	Not Determined		
Decomposition temperature	Not Determined		
Kinematic viscosity	5.0 cSt @ 40 °C		ASTM D 445
Explosive properties	Not applicable		
Oxidizing Properties	Not applicable		
<u>Other Information</u>			
Viscosity, kinematic (100°C)	Not Determined		
Pour Point	Not Determined		
VOC Content (ASTM E-1868-10)	Not Determined		
VOC content	Not Determined		

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None under normal use conditions.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information - Principle Routes of Exposure

Inhalation	Risk of serious damage to the lungs (by aspiration). Vapors may cause drowsiness and dizziness.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Irritating to skin.
Ingestion	Risk of product entering the lungs on vomiting after ingestion.
Symptoms	May be fatal if swallowed and enters airways. Moderate skin irritation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

ATEmix (oral)	13,211.00 mg/kg
ATEmix (dermal)	55,028.00 mg/kg
ATEmix (inhalation-vapor)	550.00 mg/l
ATEmix (inhalation-dust/mist)	44.70 mg/l

Acute toxicity - Product Information

May be harmful if swallowed and enters airways

Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kerosine (petroleum)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Barium bis(dinonylnaphthalenesulphonate)	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 21 mg/l (1h) (Rat)
2-Butoxyethanol	560 mg/kg (Rat)	= 220 mg/kg (Rabbit) = 2270 mg/kg (Rat)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.

Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitization	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (single exposure)	May cause drowsiness or dizziness.
Specific target organ systemic toxicity (repeated exposure)	Based on available data, the classification criteria are not met.
Aspiration hazard	Risk of serious damage to the lungs (by aspiration).
Exposure levels	See section 8 for more information
Interactive effects	None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea
2-Butoxyethanol	1840: 72 h Pseudokirchneriella subcapitata mg/L EC50	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50 1474: 96 h Oncorhynchus mykiss mg/L LC50	1698 - 1940: 24 h Daphnia magna mg/L EC50 1550: 48 h Daphnia magna mg/L EC50

Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulative potential

Chemical name	Partition coefficient
2-Butoxyethanol	0.81

Mobility

The product is insoluble and floats on water

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Safe handling and disposal methods

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Disposal of any contaminated packaging

Do not reuse empty containers.

Environmental regulations

No information available

SECTION 14: TRANSPORT INFORMATION**ADG**

UN Number	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Kerosine (PETROLEUM))
Hazard Class	9
Packing Group	III
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable
Special precautions for users	No information available
Hazchem emergency action code	+3Z
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Kerosine (PETROLEUM)), 9, III

According to special provision AU01 - Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in; (a) packagings that do not incorporate a receptacle exceeding 500 kg(L); or (b) IBCs.

IMDG

UN/ID no	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Kerosine (PETROLEUM))
Hazard Class	9
Packing Group	III
EmS-No	F-A, S-F
Vessel Stowage Location Code	A
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Kerosine (PETROLEUM)), 9, III, Marine pollutant

IATA

UN/ID no	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Kerosine (PETROLEUM))
Hazard Class	9
Packing Group	III
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Kerosine (PETROLEUM)), 9, III

SECTION 15: REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 6

New Zealand

HSNO Hazard Classification:

Not Determined

HSNO Approval Number:

Not Determined

HSNO Group Standard: None.

International Inventories

Inventory information may be utilizing alternative CAS#s or exemptions beyond those stated within this document For further information, please contact: ProductStewardship@houghtonintl.com

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Complies
KECL	Complies
IECSC	Complies
ENCS	Does not Comply
TCSI	Complies
NZIoC	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 AICS - Australian Inventory of Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 TCSI - Taiwan National Existing Chemical Inventory
 NZIoC - New Zealand Inventory of Chemicals

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Chemicals Subject to Prior Informed Consent (PIC) Not applicable

Other Information

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5

Residual oils (petroleum), solvent deasphalted	64741-95-3
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5
Residual oils (petroleum), solvent-refined	64742-01-4
Extracts (petroleum), residual oil solvent	64742-10-5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
Paraffin oils	8012-95-1
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9

SECTION 16: OTHER INFORMATION

Revision Date

09-21-2019

Revision Note

This SDS has been revised in the following section(s), Company Logo.

Key or legend to abbreviations and acronyms used in the safety data sheet

TWA	Time weighted average	STEL	Short term exposure limit
Ceiling	Maximum limit value:	(s) - Skin	Skin designation
+	Sensitizers	C	Carcinogen
STOT SE - Specific target organ systemic toxicity (Single exposure)			
STOT RE - Specific target organ systemic toxicity (repeated exposure)			
VOC - Volatile organic compounds			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet