Product data sheet

Belts · Rolls



KK732X





VSM STEARATE



		Mate	ials		Featur	es	
Grain type	Aluminium oxide	AI	Cu Ni Zn		•		
Bonding	Full-resin bonded	Aluminium	Non-ferrous metal	Unalloyed steel	Medium	Close coated	
Colour	White		metal	steei	pressure		
Backing	X-Polyester				\Diamond		
Flexibility	Sturdy	Wood	Composite	Lacquer	Also for wet grinding		
Production width	1,480 mm						

High-performance aluminium oxide abrasive on a sturdy polyester backing for universal use. KK732X is characterised by a long service life and low risk of clogging.

Grit sizes1):

				P	Р	Р	Р																	
16	20	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	

Benefits

- > The STEARATE additional layer considerably reduces chip adhesion and therefore the clogging of abrasive
- Reduced adhesive of swarf extends the service life, resulting in fewer tool changes and therefore increased productivity
- > High wear resistance

VSM · Vereinigte Schmirgelund Maschinen-Fabriken AG

Siegmundstraße 17 · 30165 Hannover · Germany T +49 511 3526 0 · F +49 511 3521 315 sales@vsmabrasives.com · www.vsmabrasives.com







