


# KV707X




## VSM NON-WOVEN




<b>Grain type</b>	Aluminium oxide / Silicon carbide
<b>Bonding</b>	Full-resin bonded
<b>Colour</b>	Coarse = Brown (AO) Medium = Red (AO) Fine = Blue (AO) Very fine = Grey (SIC)
<b>Backing</b>	X-Polyester
<b>Flexibility</b>	Sturdy
<b>Production width</b>	1,000 mm

### Materials



### Features



Surface Conditioning material on a sturdy polyester backing for improving surface finishes, deburring, rust removal, cleaning, removal of scatter marks and paint coats. Special features are a very long service life, a uniform scratch pattern, good adaptability and no clogging.

AO = Aluminium oxide    SIC = Silicon carbide

### Fineness range:<sup>1)</sup>



## Benefits

- > Ideal for calendering sheet metal plates on wide-belt sanding machines
- > Uniform surface finish
- > Good adaptability
- > Extremely long service life
- > No clogging
- > Low extensibility
- > Waterproof

**VSM · Vereinigte Schmirgel- und Maschinen-Fabriken AG**  
Siegmundstraße 17 · 30165 Hannover · Germany  
T +49 511 3526 0 · F +49 511 3521 315  
sales@vsmabrasives.com · [www.vsmabrasives.com](http://www.vsmabrasives.com)



Please scan this QR code for detailed product information.



<sup>1)</sup> Other fineness degrees upon request. Subject to technical changes.