

Name: **VSM ZK713X**

1. Features:

Grain: zirconia alumina / aluminium oxid
 Grit: 24, 36, 40, 50, 60, 80, 100, 120, P150, P180, P220, P240, P320
 Backing: sturdy polyester cloth (24, 36 - 120, P150)
 sturdy cotton cloth (P180, P220, P240, P320)
 Bonding: resin bonded
 Width: 1480 mm (24, 36 - 120, P150, P180)
 1450 mm (P220, P240, P320)

2. Application:

Material: unalloyed and low alloy steel, high-alloy steel, cast irons, aluminium alloys, brass and bronze
 Workpiece: containers, surgical tools, castings, hand tools, tubes and rods (cylindrical/square) , forged parts, metal fabrications, furniture parts/metal, parquet floor
 Grinding process: cylindrical grinding, flat grinding
 Operation: automatic grinding, powertools, manual grinding / Backstand, robot grinding

3. Advantages:

- very good grinding characteristics
- aggressive cutting
- extended lifetime
- product for consistent results on metal
- self sharpening effect

4. Further information:

VSM · Vereinigte Schmirgel- und Maschinen-Fabriken AG

Siegmundstr.17 · D-30165 Hannover
 P.O.B. 6107 · D-30061 Hannover
 Tel. + 49 511 3526 0 · Fax + 49 511 3526 315
<http://www.vsmabrasives.com> · e-mail: info@vsmabrasives.com